

TDRV005-SW-42

VxWorks Device Driver

6 Channel SSI, Incremental Encoder, Counter

Version 6.1.x

User Manual

Issue 6.1.0

February 2021

TDRV005-SW-42

VxWorks Device Driver

6 Channel SSI, Incremental Encoder, Counter

Supported Modules:

TPMC117

TPMC317

This document contains information, which is proprietary to TEWS TECHNOLOGIES GmbH. Any reproduction without written permission is forbidden.

TEWS TECHNOLOGIES GmbH has made any effort to ensure that this manual is accurate and complete. However TEWS TECHNOLOGIES GmbH reserves the right to change the product described in this document at any time without notice.

TEWS TECHNOLOGIES GmbH is not liable for any damage arising out of the application or use of the device described herein.

©2005-2021 by TEWS TECHNOLOGIES GmbH

| Issue | Description | Date |
|-------|--|-------------------|
| 1.0.0 | First Issue | December 14, 2005 |
| 1.0.1 | Examples and structures corrected | December 15, 2005 |
| 2.0.0 | New address TEWS LLC, general revision, user interface modified | July 17, 2008 |
| 2.1.0 | Support for TPMC317 added | February 12, 2009 |
| 3.0.0 | VxBus and SMP support added, initialization function tdrv005Init() added, address TEWS LLC removed | December 21, 2010 |
| 4.0.0 | VxWorks 6.9 64-Bit Support, new API Interface | January 13, 2012 |
| 5.0.0 | API Interface modified, Legacy functions removed | May 9, 2012 |
| 5.0.1 | List of recommended manuals modified | July 1, 2015 |
| 6.0.0 | VxWorks 7 Support added tdrv005GetPciInfo() added | January 10, 2017 |
| 6.1.0 | ioctl for RTP-Support modified | February 25, 2021 |

Table of Contents

| | | |
|----------|---|-----------|
| 1 | INTRODUCTION..... | 4 |
| 2 | API DOCUMENTATION | 5 |
| | 2.1 General Functions..... | 5 |
| | 2.1.1 tdrv005Open | 5 |
| | 2.1.2 tdrv005Close..... | 7 |
| | 2.1.3 tdrv005GetPciInfo | 9 |
| | 2.2 SSI Functions | 11 |
| | 2.2.1 tdrv005SsiSetup | 11 |
| | 2.2.2 tdrv005SsiRead | 14 |
| | 2.3 Counter Functions | 16 |
| | 2.3.1 tdrv005CounterSetup..... | 16 |
| | 2.3.2 tdrv005CounterRead | 20 |
| | 2.3.3 tdrv005CounterPreloadSet | 22 |
| | 2.3.4 tdrv005CounterLoad | 24 |
| | 2.3.5 tdrv005CounterReset..... | 26 |
| | 2.3.6 tdrv005CounterWaitMatch | 28 |
| | 2.3.7 tdrv005CounterWaitControlModeEvent..... | 30 |
| | 2.4 Timer Functions | 32 |
| | 2.4.1 tdrv005TimerSetup | 32 |
| | 2.4.2 tdrv005TimerStart | 34 |
| | 2.4.3 tdrv005TimerStop | 36 |
| | 2.4.4 tdrv005TimerRead | 38 |
| | 2.4.5 tdrv005TimerWait | 40 |
| | 2.4.6 tdrv005TimerMultipleChannelReadSetup..... | 42 |
| | 2.4.7 tdrv005TimerMultipleChannelReadWait..... | 44 |
| | 2.5 Digital Input Functions | 47 |
| | 2.5.1 tdrv005DigitalRead | 47 |
| | 2.5.2 tdrv005DigitalWait..... | 49 |
| | 2.6 Global Operation Functions..... | 51 |
| | 2.6.1 tdrv005GlobalChannelEnable..... | 51 |
| | 2.6.2 tdrv005GlobalChannelDisable | 53 |
| | 2.6.3 tdrv005GlobalCounterPreloadSet..... | 55 |
| | 2.6.4 tdrv005GlobalCounterLoad | 58 |
| | 2.6.5 tdrv005GlobalMultipleChannelRead..... | 60 |
| 3 | APPENDIX..... | 63 |
| | 3.1 Enable RTP-Support | 63 |

1 Introduction

The TDRV005-SW-42 VxWorks device driver software allows the operation of the supported PMCs conforming to the VxWorks I/O system specification.

The TDRV005-SW-42 release contains independent driver sources for the old legacy (pre-VxBus) and the new VxBus-enabled driver model. The VxBus-enabled driver is recommended for new developments with later VxWorks 6.x release and mandatory for VxWorks 64-bit and SMP systems.

The driver provides an application programming interface (API) and device-independent basic I/O interface with open(), close() and ioctl() functions. The basic I/O interface is only for backward compatibility with existing applications and should not be used for new developments.

The TDRV005-SW-42 device driver and its API support the following features:

- operate channels in SSI mode
 - setup and configure channel (SSI or SSI listen-only)
 - read SSI data
- operate channels in Counter mode
 - setup and configure channel
 - read counter data
 - setup preload value
 - load preload value into counter
 - reset counter
 - wait for MATCH event
 - wait for ControlMode event
- operate the onboard interval timer
 - setup and configure interval timer
 - start and stop interval timer
 - read interval timer value
 - wait for interval timer event
 - setup and use interval timer as trigger event for simultaneous multiple channel read
- enable and disable multiple channels simultaneously
- simultaneously read multiple channel values
- setup and load counter preload values simultaneously

The TDRV005-SW-42 supports the modules listed below:

| | | |
|---------|---|--------------------------|
| TPMC117 | 6 Channel SSI, Incremental Encoder, Counter | (PMC) |
| TPMC317 | 6 Channel SSI, Incremental Encoder, Counter | (PMC, Conduction Cooled) |

In this document all supported modules and devices will be called TDRV005. Specials for certain devices will be advised.

To get more information about the features and use of TDRV005 devices it is recommended to read the manuals listed below.

| |
|---|
| TEWS TECHNOLOGIES VxWorks Device Drivers - Installation Guide |
| TPMC117 / TPMC317 User Manual |

2 API Documentation

2.1 General Functions

2.1.1 tdrv005Open

NAME

tdrv005Open – opens a device.

SYNOPSIS

```
TDRV005_HANDLE tdrv005Open  
(  
    char      *DeviceName  
)
```

DESCRIPTION

Before I/O can be performed to a device, a device handle must be opened by a call to this function. If the legacy TDRV005 driver is used, this function will also install the legacy driver and create devices with the first call. The VxBus TDRV005 driver will be installed automatically by the VxBus system.

The tdrv005Open function can be called multiple times (e.g. in different tasks)

PARAMETERS

DeviceName

This parameter points to a null-terminated string that specifies the name of the device. The first TDRV005 device is named "/tdrv005/0" the second device is named "/tdrv005/1" and so on.

EXAMPLE

```
#include "tdrv005api.h"
```

```
TDRV005_HANDLE hdl;
```

```
...
```

```
...

/*
** open the specified device
*/
hdl = tdrv005Open("/tdrv005/0");
if (hdl == NULL)
{
    /* handle open error */
}
```

RETURNS

A device handle or NULL if the function fails. An error code will be stored in *errno*.

ERROR CODES

The error codes are stored in *errno*.

The error code is a standard error code set by the I/O system.

2.1.2 tdrv005Close

NAME

tdrv005Close – closes a device.

SYNOPSIS

```
TDRV005_STATUS tdrv005Close
(
    TDRV005_HANDLE      hdl
)
```

DESCRIPTION

This function closes previously opened devices.

PARAMETERS

hdl

This value specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

EXAMPLE

```
#include "tdrv005api.h"

TDRV005_HANDLE hdl;
TDRV005_STATUS result;

/*
** close the device
*/
result = tdrv005Close(hdl);
if (result != TDRV005_OK)
{
    /* handle close error */
}
```

RETURNS

TDRV005_OK on success or an appropriate system error code.

ERROR CODES

The error code is a standard error code set by the I/O system.

2.1.3 tdrv005GetPciInfo

NAME

tdrv005GetPciInfo – get information of the module PCI header

SYNOPSIS

```
TDRV005_STATUS tdrv005GetPciInfo
(
    TDRV005_HANDLE          hdl,
    TDRV005_PCIINFO_BUF    *pPciInfoBuf
)
```

DESCRIPTION

This function returns information of the module PCI header in the provided data buffer.

PARAMETERS

hdl

This argument specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

pPciInfoBuf

This argument is a pointer to the structure TDRV005_PCIINFO_BUF that receives information of the module PCI header.

```
typedef struct
{
    unsigned short    vendorId;
    unsigned short    deviceId;
    unsigned short    subSystemId;
    unsigned short    subSystemVendorId;
    int               pciBusNo;
    int               pciDevNo;
    int               pciFuncNo;
} TDRV005_PCIINFO_BUF;
```

vendorId

PCI module vendor ID.

deviceId

PCI module device ID

subSystemId
PCI module sub system ID

subSystemVendorId
PCI module sub system vendor ID

pciBusNo
Number of the PCI bus, where the module resides.

pciDevNo
PCI device number

pciFuncNo
PCI function number

EXAMPLE

```
#include "tdrv005api.h"

TDRV005_HANDLE      hdl;
TDRV005_STATUS      result;
TDRV005_PCIINFO_BUF pciInfoBuf

/*
** get module PCI information
*/
result = tdrv005GetPciInfo( hdl, &pciInfoBuf );
if (result != TDRV005_OK)
{
    /* handle error */
}
```

RETURN VALUE

On success, TDRV005_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

| Error Code | Description |
|----------------------------|--|
| TDRV005_ERR_INVALID_HANDLE | The specified device handle is invalid |

2.2 SSI Functions

2.2.1 tdrv005SsiSetup

NAME

tdrv005SsiSetup – set up a channel for SSI operation.

SYNOPSIS

```
TDRV005_STATUS tdrv005SsiSetup
(
    TDRV005_HANDLE          hdl,
    unsigned char           Channel,
    TDRV005_SSI_SETUP      *Options
)
```

DESCRIPTION

This function sets up a specific channel to the provided SSI configuration. The function returns immediately to the caller after setting up the corresponding channel.

The SSI channel is not enabled by this command. This must be done by a subsequent call to tdrv005GlobalChannelEnable (see chapter 2.6.1)

PARAMETERS

hdl

This value specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

Channel

This value specifies the channel which should be affected. The pre-defined values (TDRV005_CH0 – TDRV005_CH5) must be used. Only one channel may be specified.

Options

This value specifies the necessary configuration options in the structure TDRV005_SSI_SETUP with the following layout:

```
typedef struct
{
    TDRV005_SSI_MODE           Mode;
    unsigned char              NumberOfDataBits;
    TDRV005_SSI_CODING         Coding;
    unsigned char              ZeroBits;
    TDRV005_SSI_PARITY         Parity;
    unsigned char              ClockRate;
} TDRV005_SSI_SETUP;
```

Mode

This value specifies the desired operation mode of the SSI interface. Possible values are:

| Value | Description |
|-------------------------|--|
| TDRV005_MODE_STANDARD | Standard SSI operation |
| TDRV005_MODE_LISTENONLY | SSI interface operates in listen-only mode |

NumberOfDataBits

This value specifies the number of data bits to use. Possible values are between 1 and 32.

Coding

This value specifies the desired coding format. Possible values are:

| Value | Description |
|-----------------------|--|
| TDRV005_CODING_BINARY | Binary coding is used |
| TDRV005_CODING_GRAY | Gray coding is used, data is converted into binary |

ZeroBits

This value specifies the number of zero bits to use in combination with parity. Possible values are either 0 or 1.

Parity

This value specifies what kind of parity bit should be used. Possible values are:

| Value | Description |
|---------------------|----------------------------|
| TDRV005_PARITY_NONE | No parity bit is used |
| TDRV005_PARITY_EVEN | An even parity bit is used |
| TDRV005_PARITY_ODD | An odd parity bit is used |

ClockRate

This value specifies the clock rate for the encoder's serial clock speed. The clock can be programmed in steps of 1µs in the range of 1 to 15.

EXAMPLE

```
#include "tdrv005api.h"

TDRV005_HANDLE    hdl;
TDRV005_STATUS    result;
TDRV005_SSI_SETUP Options;

/*
** setup the counter with appropriate options
*/
Options.Mode                = TDRV005_MODE_STANDARD;
Options.NumberOfDataBits    = 32;
Options.Coding               = TDRV005_CODING_BINARY;
Options.ZeroBits             = 1;
Options.Parity               = TDRV005_PARITY_NONE;
Options.ClockRate            = 10;

result = tdrv005SsiSetup(hdl, TDRV005_CH0, &Options);
if (result != TDRV005_OK)
{
    /* handle configuration error */
}

```

RETURNS

On success, TDRV005_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

| Error Code | Description |
|----------------------------|--|
| TDRV005_ERR_INVALID_HANDLE | The specified device handle is invalid |
| TDRV005_ERR_INVAL | Invalid parameter specified |

2.2.2 tdrv005SsiRead

NAME

tdrv005SsiRead – read the value of an SSI channel.

SYNOPSIS

```
TDRV005_STATUS tdrv005SsiRead
(
    TDRV005_HANDLE          hdl,
    unsigned char           Channel,
    int                     Timeout,
    unsigned int            *Data,
    unsigned int            *Status
)
```

DESCRIPTION

This function reads the value of the data register of corresponding channel. Only the number of previously configured data bits is valid. The function returns to the caller after the desired channel is read or the specified timeout occurred.

PARAMETERS

hdl

This value specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

Channel

This value specifies the channel which should be affected. The pre-defined values (TDRV005_CH0 – TDRV005_CH5) must be used. Only one channel may be specified.

Timeout

This value specifies the timeout in milliseconds. If the function should wait indefinitely for the data to be valid, *TDRV005_WAIT_FOREVER* must be specified.

Data

This parameter points to an unsigned int value where the data register content is stored.

Status

This parameter points to an unsigned int value where the status register content is stored.

EXAMPLE

```
#include "tdrv005api.h"

TDRV005_HANDLE    hdl;
TDRV005_STATUS    result;
unsigned int      ssiValue;
unsigned int      ssiStatus;

/*
** read the current counter value
*/
result = tdrv005SsiRead(hdl,
                        TDRV005_CH0,
                        TDRV005_WAIT_FOREVER,
                        &ssiValue,
                        &ssiStatus);

if (result == TDRV005_OK)
{
    printf( "SSI Value = 0x%08X\n", ssiValue );
    printf( "SSI Status = 0x%08X\n", ssiStatus );
}
```

RETURNS

On success, TDRV005_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

| Error Code | Description |
|----------------------------|--|
| TDRV005_ERR_INVALID_HANDLE | The specified device handle is invalid |
| TDRV005_ERR_INVALID | Invalid parameter specified |
| TDRV005_ERR_BUSY | Channel is not configured to SSI mode, or there is another job in progress |

2.3 Counter Functions

2.3.1 tdrv005CounterSetup

NAME

tdrv005CounterSetup – set up a channel for counter operation

SYNOPSIS

```
TDRV005_STATUS tdrv005CounterSetup
(
    TDRV005_HANDLE          hdl,
    unsigned char           Channel,
    TDRV005_COUNTER_SETUP *Options
)
```

DESCRIPTION

This function sets up a specific channel to the provided counter configuration. The function returns immediately to the caller after setting up the corresponding channel.

The counter channel is not enabled by this command. This must be done by a subsequent call to tdrv005GlobalChannelEnable (see chapter 2.6.1)

PARAMETERS

hdl

This value specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

Channel

This value specifies the channel which should be affected. The pre-defined values (TDRV005_CH0 – TDRV005_CH5) must be used. Only one channel may be specified.

Options

This value specifies the necessary configuration options in the structure *TDRV005_COUNTER_SETUP* with the following layout:

```
typedef struct
{
    unsigned char      Polarity;
    TDRV005_CNT_INPUT  InputMode;
    TDRV005_CNT_INDEX  IndexControlMode;
    TDRV005_CNT_SCM    SpecialCountMode;
    TDRV005_CNT_CLKDIV ClockPrescaler;
} TDRV005_COUNTER_SETUP;
```

Polarity

This value specifies the input polarity of the specified channel. The Input Polarity Control can be used to adapt the input to the input source polarity of A, B and I. Use the following predefined values to generate an OR'ed polarity value.

| Value | Description |
|------------------------|---|
| TDRV005_POLARITY_A_LOW | low-active signal, default is high-active |
| TDRV005_POLARITY_B_LOW | low-active signal, default is high-active |
| TDRV005_POLARITY_I_LOW | low-active signal, default is high-active |

InputMode

The Input Mode determines the input source and how the counter interprets these input signals. Possible values are:

| Value | Description | Input Source |
|-----------------------------|---------------------|--------------------------|
| TDRV005_INPUT_TIMER_UP | Timer mode Up | internal clock prescaler |
| TDRV005_INPUT_TIMER_DOWN | Timer mode Down | internal clock prescaler |
| TDRV005_INPUT_DIRECTION | Direction count | Input A & Input B |
| TDRV005_INPUT_UPDOWN | Up/Down count | Input A & Input B |
| TDRV005_INPUT_QUADRATURE_1X | Quadrature count 1x | Input A & Input B |
| TDRV005_INPUT_QUADRATURE_2X | Quadrature count 2x | Input A & Input B |
| TDRV005_INPUT_QUADRATURE_4X | Quadrature count 4x | Input A & Input B |

IndexControlMode

The Index Control Mode determines how the counter interprets events on the I-input. Possible values are:

| Value | Description |
|---------------------------------|---|
| TDRV005_ICM_NO_INDEX_CONTROL | no I-control |
| TDRV005_ICM_LOAD_ON_INDEX | load on index signal |
| TDRV005_ICM_LATCH_ON_INDEX | latch on index signal |
| TDRV005_ICM_GATE_ON_INDEX | gate on index signal |
| TDRV005_ICM_RESET_ON_INDEX | reset on index signal |
| TDRV005_ICM_REFERENCE_MODE | reference mode (quadrature input mode only) |
| TDRV005_ICM_AUTO_REFERENCE_MODE | auto-reference mode (quadrature input mode only) |
| TDRV005_ICM_INDEX_MODE | index mode (quadrature input mode only) |

SpecialCountMode

This value specifies the desired special count mode. Possible values are:

| Value | Description |
|-----------------------------|--|
| TDRV005_SCM_CYCLING_COUNTER | No special count mode, cycling counter |
| TDRV005_SCM_DIVIDE_BY_N | Divide-by-N mode |
| TDRV005_SCM_SINGLE_CYCLE | Single cycle mode |

ClockPrescaler

This value specifies the internal clock prescaler to be used. Possible values are:

| Value | Description |
|-------------------|----------------------------|
| TDRV005_CLKDIV_1X | Prescaler 1x, 32 MHz clock |
| TDRV005_CLKDIV_2X | Prescaler 2x, 16 MHz clock |
| TDRV005_CLKDIV_4X | Prescaler 4x, 8 MHz clock |
| TDRV005_CLKDIV_8X | Prescaler 8x, 4 MHz clock |

EXAMPLE

```
#include "tdrv005api.h"

TDRV005_HANDLE      hdl;
TDRV005_STATUS      result;
TDRV005_COUNTER_SETUP Options;

...
```

```

...

/*
** setup the counter with appropriate options
*/
Options.Polarity          = TDRV005_POLARITY_A_LOW |
                           TDRV005_POLARITY_B_LOW |
                           TDRV005_POLARITY_I_LOW;

Options.InputMode         = TDRV005_INPUT_UPDOWN;
Options.IndexControlMode  = TDRV005_ICM_NO_INDEX_CONTROL;
Options.SpecialCountMode  = TDRV005_SCM_CYCLING_COUNTER;
Options.ClockPrescaler    = TDRV005_CLKDIV_8X;

result = tdrv005CounterSetup(hdl, TDRV005_CH0, &Options);
if (result != TDRV005_OK)
{
    /* handle configuration error */
}

```

RETURNS

On success, TDRV005_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

| Error Code | Description |
|----------------------------|--|
| TDRV005_ERR_INVALID_HANDLE | The specified device handle is invalid |
| TDRV005_ERR_INVALID | Invalid parameter specified |

2.3.2 tdrv005CounterRead

NAME

tdrv005CounterRead – read the value of a counter channel

SYNOPSIS

```
TDRV005_STATUS tdrv005CounterRead
(
    TDRV005_HANDLE          hdl,
    unsigned char           Channel,
    unsigned int            *Data,
    unsigned int            *Status
)
```

DESCRIPTION

This function reads the value of the corresponding channel's data register. The function returns immediately to the caller.

PARAMETERS

hdl

This value specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

Channel

This value specifies the channel on which the specified event should occur. The pre-defined values (TDRV005_CH0 – TDRV005_CH5) must be used. Only one channel may be specified.

Data

This parameter points to an unsigned int value where the data register content is stored.

Status

This parameter points to an unsigned int value where the status register content is stored.

EXAMPLE

```
#include "tdrv005api.h"

TDRV005_HANDLE    hdl;
TDRV005_STATUS    result;
unsigned int      CounterValue, Status;

/*
** read the current counter value
*/
result = tdrv005CounterRead( hdl,
                             TDRV005_CH0,
                             &CounterValue,
                             &Status);

if (result == TDRV005_OK)
{
    printf( "Counter Value = 0x%08X\n", CounterValue );
    printf( "Status Value = 0x%08X\n", Status );
}

```

RETURNS

On success, TDRV005_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

| Error Code | Description |
|----------------------------|---|
| TDRV005_ERR_INVALID_HANDLE | The specified device handle is invalid |
| TDRV005_ERR_INVALID | Invalid parameter specified |
| TDRV005_ERR_BUSY | Channel is not configured to counter mode |

2.3.3 tdrv005CounterPreloadSet

NAME

tdrv005CounterPreloadSet – set the preload register of a counter channel

SYNOPSIS

```
TDRV005_STATUS tdrv005CounterPreloadSet
(
    TDRV005_HANDLE      hdl,
    unsigned char       Channel,
    unsigned int        PreloadValue
)
```

DESCRIPTION

This function sets the counter's preload register to the supplied value. The function returns immediately to the caller.

PARAMETERS

hdl

This value specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

Channel

This value specifies the channel which should be affected. The pre-defined values (TDRV005_CH0 – TDRV005_CH5) must be used. Only one channel may be specified.

PreloadValue

This value specifies the new value of the channel's preload register.

EXAMPLE

```
#include "tdrv005api.h"

TDRV005_HANDLE      hdl;
TDRV005_STATUS      result;
unsigned int        PreloadValue;

...
```

```
...

/*
** load counter value
*/
PreloadValue = 0x12345678;

result = tdrv005CounterPreloadSet(hdl, TDRV005_CH0, PreloadValue);
if (result != TDRV005_OK)
{
    /* handle error */
}
```

RETURNS

On success, TDRV005_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

| Error Code | Description |
|----------------------------|---|
| TDRV005_ERR_INVALID_HANDLE | The specified device handle is invalid |
| TDRV005_ERR_INVALID | Invalid parameter specified |
| TDRV005_ERR_BUSY | Channel is not configured to counter mode |

2.3.4 tdrv005CounterLoad

NAME

tdrv005CounterLoad – load the preload register into the counter channel

SYNOPSIS

```
TDRV005_STATUS tdrv005CounterLoad
(
    TDRV005_HANDLE          hdl,
    unsigned char           Channel
)
```

DESCRIPTION

This function loads the counter to the previously specified value of the counter preload register. The function returns immediately to the caller. To simultaneously load multiple channels, please refer to chapter 2.6.5 `tdrv005GlobalMultipleChannelRead()`.

PARAMETERS

hdl

This value specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

Channel

This value specifies the channel which should be affected. The pre-defined values (TDRV005_CH0 – TDRV005_CH5) must be used. Only one channel may be specified.

EXAMPLE

```
#include "tdrv005api.h"

TDRV005_HANDLE    hdl;
TDRV005_STATUS    result;

...
```



```
...  
  
/*  
** load counter value  
*/  
result = tdrv005CounterLoad(hdl, TDRV005_CH0);  
if (result != TDRV005_OK)  
{  
    /* handle error */  
}
```

RETURNS

On success, TDRV005_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

| Error Code | Description |
|----------------------------|---|
| TDRV005_ERR_INVALID_HANDLE | The specified device handle is invalid |
| TDRV005_ERR_INVAL | Invalid parameter specified |
| TDRV005_ERR_BUSY | Channel is not configured to counter mode |

2.3.5 tdrv005CounterReset

NAME

tdrv005CounterReset – reset the counter channel

SYNOPSIS

```
TDRV005_STATUS tdrv005CounterReset
(
    TDRV005_HANDLE          hdl,
    unsigned char           Channel
)
```

DESCRIPTION

This function resets the counter value of the specified channel. The function returns immediately to the caller.

PARAMETERS

hdl

This value specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

Channel

This value specifies the channel which should be affected. The pre-defined values (TDRV005_CH0 – TDRV005_CH5) must be used. Only one channel may be specified.

EXAMPLE

```
#include "tdrv005api.h"

TDRV005_HANDLE    hdl;
TDRV005_STATUS    result;

/*
** reset counter value
*/
result = tdrv005CounterReset(hdl, TDRV005_CH0);
if (result != TDRV005_OK)
{
    /* handle error */
}
```

RETURNS

On success, TDRV005_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

| Error Code | Description |
|----------------------------|---|
| TDRV005_ERR_INVALID_HANDLE | The specified device handle is invalid |
| TDRV005_ERR_INVALID | Invalid parameter specified |
| TDRV005_ERR_BUSY | Channel is not configured to counter mode |

2.3.6 tdrv005CounterWaitMatch

NAME

tdrv005CounterWaitMatch – wait for a counter-match event

SYNOPSIS

```
TDRV005_STATUS tdrv005CounterWaitMatch
(
    TDRV005_HANDLE          hdl,
    unsigned char           Channel,
    unsigned int            CompareValue,
    int                     Timeout
)
```

DESCRIPTION

Waits until the counter value matches the provided counter compare value. The function returns to the caller if the counter matches the provided compare value, or the specified timeout occurred.

PARAMETERS

hdl

This value specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

Channel

This value specifies the channel on which the specified event should occur. The pre-defined values (TDRV005_CH0 – TDRV005_CH5) must be used. Only one channel may be specified.

CompareValue

This parameter specifies the value to which the counter should be compared.

Timeout

This value specifies the timeout in milliseconds. If the function should wait indefinitely for the event to occur, TDRV005_WAIT_FOREVER must be specified.

EXAMPLE

```
#include "tdrv005api.h"

TDRV005_HANDLE    hdl;
TDRV005_STATUS    result;
unsigned int       MatchValue;

/*
** wait indefinitely for counter match event
*/
MatchValue = 0x12345678;

result = tdrv005CounterWaitMatch(hdl,
                                  TDRV005_CH0,
                                  MatchValue,
                                  TDRV005_WAIT_FOREVER);

if (result != TDRV005_OK)
{
    /* handle error */
}
```

RETURNS

On success, TDRV005_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

| Error Code | Description |
|----------------------------|--|
| TDRV005_ERR_INVALID_HANDLE | The specified device handle is invalid |
| TDRV005_ERR_INVAL | Invalid parameter specified |
| TDRV005_ERR_BUSY | Channel is not configured to counter mode, or a counter-match job is already pending |
| TDRV005_ERR_TIMEOUT | The event has not occurred, timeout |

2.3.7 tdrv005CounterWaitControlModeEvent

NAME

tdrv005CounterWaitControlModeEvent – wait for a counter-control-mode event

SYNOPSIS

```
TDRV005_STATUS tdrv005CounterWaitControlModeEvent
(
    TDRV005_HANDLE          hdl,
    unsigned char           Channel,
    int                     Timeout
)
```

DESCRIPTION

Wait for the control mode event of the counter. The function returns to the caller if the configured control mode event or the specified timeout occurred.

PARAMETERS

hdl

This value specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

Channel

This value specifies the channel on which the specified event should occur. The pre-defined values (TDRV005_CH0 – TDRV005_CH5) must be used. Only one channel may be specified.

Timeout

This value specifies the timeout in milliseconds. If the function should wait indefinitely for the event to occur, TDRV005_WAIT_FOREVER must be specified.

EXAMPLE

```
#include "tdrv005api.h"

TDRV005_HANDLE    hdl;
TDRV005_STATUS    result;

/*
** wait indefinitely for counter control mode event
*/
result = tdrv005CounterWaitControlModeEvent(hdl,
                                             TDRV005_CH0,
                                             TDRV005_WAIT_FOREVER);

if (result != TDRV005_OK)
{
    /* handle error */
}
```

RETURNS

On success, TDRV005_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

| Error Code | Description |
|----------------------------|--|
| TDRV005_ERR_INVALID_HANDLE | The specified device handle is invalid |
| TDRV005_ERR_INVALID | Invalid parameter specified |
| TDRV005_ERR_BUSY | Channel is not configured to counter mode, or a counter-match job is already pending |
| TDRV005_ERR_TIMEOUT | The event has not occurred, timeout |

2.4 Timer Functions

2.4.1 tdrv005TimerSetup

NAME

tdrv005TimerSetup – set up the timer

SYNOPSIS

```
TDRV005_STATUS tdrv005TimerSetup
(
    TDRV005_HANDLE          hdl,
    TDRV005_CNT_CLKFRQ     ClockFrequency,
    unsigned short          PreloadValue
)
```

DESCRIPTION

This function sets up the onboard timer to the provided configuration. The function returns immediately to the caller. The interval timer remains stopped after a call to this function.

PARAMETERS

hdl

This value specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

ClockFrequency

This value specifies the clock frequency used as clock source for the timer. Possible values are:

| Value | Description |
|---------------------|-------------|
| TDRV005_CLKFRQ_1MHZ | 1 MHz clock |
| TDRV005_CLKFRQ_2MHZ | 2 MHz clock |
| TDRV005_CLKFRQ_4MHZ | 4 MHz clock |
| TDRV005_CLKFRQ_8MHZ | 8 MHz clock |

PreloadValue

This value specifies the preload value of the timer. If the interval timer is running, this value is loaded automatically every time the timer expires. The preload value is of 16bit width.

EXAMPLE

```
#include "tdrv005api.h"

TDRV005_HANDLE    hdl;
TDRV005_STATUS    result;

/*
** setup the interval timer with an interrupt frequency of 100 Hz
*/
result = tdrv005TimerSetup( hdl,
                            TDRV005_CLKFRQ_1MHZ,
                            10000);

if (result != TDRV005_OK)
{
    /* handle error */
}
```

RETURN VALUE

On success, TDRV005_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

| Error Code | Description |
|----------------------------|--|
| TDRV005_ERR_INVALID_HANDLE | The specified device handle is invalid |
| TDRV005_ERR_INVAL | Invalid parameter specified |

2.4.2 tdrv005TimerStart

NAME

tdrv005TimerStart – start the timer

SYNOPSIS

```
TDRV005_STATUS tdrv005TimerStart
(
    TDRV005_HANDLE      hdl
)
```

DESCRIPTION

Start the previously configured timer. The function returns immediately to the caller.

PARAMETERS

hdl

This value specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

EXAMPLE

```
#include "tdrv005api.h"

TDRV005_HANDLE      hdl;
TDRV005_STATUS      result;

/*
** start the previously configured interval timer
*/
result = tdrv005TimerStart(hdl);
if (result != TDRV005_OK)
{
    /* handle error */
}
```

RETURN VALUE

On success, TDRV005_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

| Error Code | Description |
|----------------------------|--|
| TDRV005_ERR_INVALID_HANDLE | The specified device handle is invalid |
| TDRV005_ERR_NOT_CONFIG | The timer was not configured properly |

2.4.3 tdrv005TimerStop

NAME

tdrv005TimerStop – stop the timer

SYNOPSIS

```
TDRV005_STATUS tdrv005TimerStop
(
    TDRV005_HANDLE      hdl
)
```

DESCRIPTION

Stop the previously configured timer. The function returns immediately to the caller.

PARAMETERS

hdl

This value specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

EXAMPLE

```
#include "tdrv005api.h"

TDRV005_HANDLE      hdl;
TDRV005_STATUS      result;

/*
** stop the interval timer
*/
result = tdrv005TimerStop(hdl);
if (result != TDRV005_OK)
{
    /* handle error */
}
```

RETURN VALUE

On success, TDRV005_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

| Error Code | Description |
|----------------------------|--|
| TDRV005_ERR_INVALID_HANDLE | The specified device handle is invalid |
| TDRV005_ERR_NOT_CONFIG | The timer was not configured properly |

2.4.4 tdrv005TimerRead

NAME

tdrv005TimerRead – read the current timer value

SYNOPSIS

```
TDRV005_STATUS tdrv005TimerRead
(
    TDRV005_HANDLE      hdl,
    unsigned short      *Data
)
```

DESCRIPTION

Read the current value of the timer. The function returns immediately to the caller.

PARAMETERS

hdl

This value specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

Data

This parameter points to an unsigned short value where the data register content is stored.

EXAMPLE

```
#include "tdrv005api.h"

TDRV005_HANDLE      hdl;
TDRV005_STATUS      result;
unsigned short      TimerValue;

/*
** read the current interval timer value
*/
result = tdrv005TimerRead(hdl, &TimerValue);
if (result == TDRV005_OK)
{
    printf( "Timer Value = 0x%04X\n", TimerValue );
}
```

RETURN VALUE

On success, TDRV005_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

| Error Code | Description |
|----------------------------|--|
| TDRV005_ERR_INVALID_HANDLE | The specified device handle is invalid |
| TDRV005_ERR_INVALID | Invalid parameter specified |

2.4.5 tdrv005TimerWait

NAME

tdrv005TimerWait – wait for a timer event

SYNOPSIS

```
TDRV005_STATUS tdrv005TimerWait
(
    TDRV005_HANDLE      hdl,
    int                  Timeout
)
```

DESCRIPTION

Wait for the timer event or the specified timeout to occur. The function returns to the caller if the timer has expired, or the specified timeout occurred.

PARAMETERS

hdl

This value specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

Timeout

This value specifies the timeout in milliseconds. If the function should wait indefinitely for the event to occur, TDRV005_WAIT_FOREVER must be specified.

EXAMPLE

```
#include "tdrv005api.h"

TDRV005_HANDLE      hdl;
TDRV005_STATUS      result;

/*
** wait indefinitely for an interval timer event
*/
result = tdrv005TimerWait(hdl, TDRV005_WAIT_FOREVER);
if (result != TDRV005_OK)
{
    /* handle error */
}
```

RETURN VALUE

On success, TDRV005_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

| Error Code | Description |
|----------------------------|---|
| TDRV005_ERR_INVALID_HANDLE | The specified device handle is invalid |
| TDRV005_ERR_NOT_CONFIG | The timer was not configured properly |
| TDRV005_ERR_TIMEOUT | The timer event has not occurred, timeout |
| TDRV005_ERR_NOT_RUNNING | The timer is not running |

2.4.6 tdrv005TimerMultipleChannelReadSetup

NAME

tdrv005TimerMultipleChannelReadSetup – set up channels for multiple read

SYNOPSIS

```
TDRV005_STATUS tdrv005TimerMultipleChannelReadSetup
(
    TDRV005_HANDLE          hdl,
    unsigned char           Channels
)
```

DESCRIPTION

Configure specified channels for simultaneous sampling triggered by the timer. The function returns immediately to the caller.

Channels configured to SSI listen-only mode may not be used with this function.

PARAMETERS

hdl

This value specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

Channels

This value specifies the channels which should be read simultaneously. The pre-defined values (TDRV005_CH0 – TDRV005_CH5) must be used. Multiple channels may be OR'ed to one value.

EXAMPLE

```
#include "tdrv005api.h"

TDRV005_HANDLE    hdl;
TDRV005_STATUS    result;

...
```

```
...

/*
** setup channels 0+5 for simultaneous sampling triggered by timer
*/
result = tdrv005TimerMultipleChannelReadSetup( hdl,
                                                TDRV005_CH0 | TDRV005_CH5);

if (result != TDRV005_OK)
{
    /* handle error */
}
```

RETURN VALUE

On success, TDRV005_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

| Error Code | Description |
|----------------------------|---|
| TDRV005_ERR_INVALID_HANDLE | The specified device handle is invalid |
| TDRV005_ERR_INVALID | Invalid parameter specified |
| TDRV005_ERR_BUSY | Specified channel is busy with an SSI job |

2.4.7 tdrv005TimerMultipleChannelReadWait

NAME

tdrv005TimerMultipleChannelReadWait – wait for the simultaneous data timer event

SYNOPSIS

```
TDRV005_STATUS tdrv005TimerMultipleChannelReadWait
(
    TDRV005_HANDLE          hdl,
    TDRV005_MULTIPLEVALUES *MultipleValues,
    unsigned int            *Timestamp,
    int                     *MoreDataAvailable
)
```

DESCRIPTION

Return the values of simultaneously sampled channels. An array to store all channel values must be supplied to this function. The function waits for the timer event to occur on which the previously configured channels are sampled, or the timeout (1 second) occurred. Before using this function the timer must be configured properly.

PARAMETERS

hdl

This value specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

MultipleValues

This is a pointer to a TDRV005_MULTIPLEVALUES structure, where the read values are stored. Note that only the previously configured channels return valid data, other data entries must be ignored. The TDRV005_MULTIPLEVALUES structure has the following layout:

```
typedef struct
{
    TDRV005_VALUE_BUF Channel[6];
} TDRV005_MULTIPLEVALUES;
```

Channel

This parameter is an array of a TDRV005_VALUE_BUF structure which holds the returned channel data. The value for channel 0 is returned at array index 0, channel 5's value is located at array index 5. The TDRV005_VALUE_BUF structure has the following layout:

```
typedef struct
{
    unsigned int    Value;
    unsigned int    Status;
} TDRV005_VALUE_BUF;
```

Value

This parameter holds the returned channel value.

Status

This parameter holds the returned channel status.

Timestamp

This is a pointer to an unsigned int value where the number of occurred timer interrupts is returned.

MoreDataAvailable

This is a pointer to a boolean integer value. The value is TRUE if additional data is available. This might happen if the timer event triggering the multiple-channel-read operation appears too fast. An additional call to `tdrv005timerMultipleChannelReadWait` must be performed.

EXAMPLE

```
#include "tdrv005api.h"

TDRV005_HANDLE    hdl;
TDRV005_STATUS    result;
int               MoreDataAvailable;
unsigned int      Timestamp;
TDRV005_MULTIPLEVALUES MultipleValues;
```

...

```

...

/*
** read channels triggered by timer
*/
result = tdrv005TimerMultipleChannelReadWait(hdl,
                                              &MultipleValues,
                                              &Timestamp,
                                              &MoreDataAvailable);

if (result == TDRV005_OK)
{
    printf( "Timestamp = %d\n", Timestamp);
    printf( "Channel(0) = 0x%08X\n", MultipleValues.Channel[0].Value);
    printf( "Channel(5) = 0x%08X\n", MultipleValues.Channel[5].Value);
}
else
{
    /* handle error */
}

```

RETURN VALUE

On success, TDRV005_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

| Error Code | Description |
|----------------------------|---|
| TDRV005_ERR_INVALID_HANDLE | The specified device handle is invalid |
| TDRV005_ERR_INVAL | Invalid parameter specified |
| TDRV005_ERR_BUSY | Another job is already pending |
| TDRV005_ERR_TIMEOUT | The timer event has not occurred, timeout |
| TDRV005_ERR_NOT_CONFIG | The timer was not configured properly |

2.5 Digital Input Functions

2.5.1 tdrv005DigitalRead

Name

tdrv005DigitalRead – read the digital input lines

Synopsis

```
TDRV005_STATUS tdrv005DigitalRead
(
    TDRV005_HANDLE          hdl,
    unsigned char           *Data
)
```

Description

Read the current values of all digital input lines. The function returns immediately to the caller.

Parameters

hdl

This value specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

Data

This parameter points to an *unsigned char* value where the data register content is stored. Channel 0 is represented by bit 0, channel 5 is represented by bit 5 of the returned byte value.

Example

```
#include "tdrv005api.h"

TDRV005_HANDLE    hdl;
TDRV005_STATUS    result;
unsigned char     DigitalValue;

...
```

```
...

/*
** read the current interval timer value
*/
result = tdrv005DigitalRead(hdl, &DigitalValue);
if (result == TDRV005_OK)
{
    printf( "Digital Value = 0x%02X\n", DigitalValue );
}
```

RETURN VALUE

On success, TDRV005_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

| Error Code | Description |
|----------------------------|--|
| TDRV005_ERR_INVALID_HANDLE | The specified device handle is invalid |
| TDRV005_ERR_INVAL | Invalid parameter specified |

2.5.2 tdrv005DigitalWait

Name

tdrv005DigitalWait – wait for an event on a digital input line

Synopsis

```
TDRV005_STATUS tdrv005DigitalWait
(
    TDRV005_HANDLE          hdl,
    unsigned char           Channel,
    TDRV005_TRANSITION      Transition,
    int                     Timeout
)
```

Description

Wait for the specified transition (rising or falling edge) on the specified digital input line. The function returns to the caller if the specified transition or the specified timeout occurred.

Parameters

hdl

This value specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

Channel

This value specifies the channel on which the specified event should occur. The pre-defined values (TDRV005_CH0 – TDRV005_CH5) must be used. Only one channel may be specified.

Transition

This value specifies the transition on which the specified event should occur.

| Value | Description |
|-------------------------|-------------------------------|
| TDRV005_TR_RISING_EDGE | Rising edge on digital input |
| TDRV005_TR_FALLING_EDGE | Falling edge on digital input |

Timeout

This value specifies the timeout in milliseconds. If the function should wait indefinitely for the event to occur, TDRV005_WAIT_FOREVER must be specified.

Example

```
#include "tdrv005api.h"

TDRV005_HANDLE    hdl;
TDRV005_STATUS    result;

/*
** wait indefinitely for a rising edge on digital input of channel 1
*/
result = tdrv005DigitalWait(hdl,
                            TDRV005_CH1,
                            TDRV005_TR_RISING_EDGE,
                            TDRV005_WAIT_FOREVER);

if (result != TDRV005_OK)
{
    /* handle error */
}
```

RETURN VALUE

On success, TDRV005_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

| Error Code | Description |
|----------------------------|--|
| TDRV005_ERR_INVALID_HANDLE | The specified device handle is invalid |
| TDRV005_ERR_INVALID | Invalid parameter specified |
| TDRV005_ERR_TIMEOUT | The event has not occurred, timeout |

2.6 Global Operation Functions

2.6.1 tdrv005GlobalChannelEnable

Name

tdrv005GlobalChannelEnable – globally enable multiple channels

Synopsis

```
TDRV005_STATUS tdrv005GlobalChannelEnable
(
    TDRV005_HANDLE          hdl,
    unsigned char           Channels
)
```

Description

Enable multiple channels (SSI or Counter) simultaneously. The function returns immediately to the caller.

Parameters

hdl

This value specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

Channels

This value specifies the channels which should be enabled. The pre-defined values (TDRV005_CH0 – TDRV005_CH5) must be used. Multiple channels may be OR'ed to one value.

Example

```
#include "tdrv005api.h"

TDRV005_HANDLE    hdl;
TDRV005_STATUS    result;

...
```

```
...  
  
/*  
** enable channel 0 and channel 5  
*/  
result = tdrv005GlobalChannelEnable ( hdl,  
                                     TDRV005_CH0 | TDRV005_CH5);  
  
if (result != TDRV005_OK)  
{  
    /* handle error */  
}
```

RETURN VALUE

On success, TDRV005_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

| Error Code | Description |
|----------------------------|--|
| TDRV005_ERR_INVALID_HANDLE | The specified device handle is invalid |
| TDRV005_ERR_INVALID | Invalid parameter specified |

2.6.2 tdrv005GlobalChannelDisable

Name

tdrv005GlobalChannelDisable – globally disable multiple channels

Synopsis

```
TDRV005_STATUS tdrv005GlobalChannelDisable  
(  
    TDRV005_HANDLE          hdl,  
    unsigned char           Channels  
)
```

Description

Disable multiple channels (SSI or Counter) simultaneously. The function returns immediately to the caller.

Parameters

hdl

This value specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

Channels

This value specifies the channels which should be disabled. The pre-defined values (TDRV005_CH0 – TDRV005_CH5) must be used. Multiple channels may be OR'ed to one value.

Example

```
#include "tdrv005api.h"  
  
TDRV005_HANDLE    hdl;  
TDRV005_STATUS    result;  
  
...
```

```
...  
  
/*  
** disable channel 0 and channel 5  
*/  
result = tdrv005GlobalChannelDisable (hdl,  
                                     TDRV005_CH0 | TDRV005_CH5);  
  
if (result != TDRV005_OK)  
{  
    /* handle error */  
}
```

RETURN VALUE

On success, TDRV005_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

| Error Code | Description |
|----------------------------|--|
| TDRV005_ERR_INVALID_HANDLE | The specified device handle is invalid |
| TDRV005_ERR_INVAL | Invalid parameter specified |

2.6.3 tdrv005GlobalCounterPreloadSet

Name

tdrv005GlobalCounterPreloadSet – globally set counter preload registers

Synopsis

```
TDRV005_STATUS tdrv005GlobalCounterPreloadSet
(
    TDRV005_HANDLE          hdl,
    unsigned char           Channels,
    TDRV005_MULTIPLEVALUES *MultipleValues
)
```

Description

Perform a simultaneous setup of the preload registers of specified counter channels. The desired values must be supplied to this function as well as the channel numbers which are affected. The function returns immediately to the caller.

Parameters

hdl

This value specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

Channels

This value specifies the channels which should be preloaded. The pre-defined values (TDRV005_CH0 – TDRV005_CH5) must be used. Multiple channels may be OR'ed to one value.

MultipleValues

This is a pointer to a TDRV005_MULTIPLEVALUES structure, where the read values are stored. The TDRV005_MULTIPLEVALUES structure has the following layout:

```
typedef struct
{
    TDRV005_VALUE_BUF Channel[6];
} TDRV005_MULTIPLEVALUES;
```

Channel

This parameter is an array of a TDRV005_VALUE_BUF structure which holds the preload data. The value for channel 0 is located at array index 0, channel 5's value is located at array index 5. The TDRV005_VALUE_BUF structure has the following layout:

```
typedef struct
{
    unsigned int    Value;
    unsigned int    Status;
} TDRV005_VALUE_BUF;
```

Value

This parameter holds the preload channel value.

Status

This parameter is not used for this function.

Example

```
#include "tdrv005api.h"

TDRV005_HANDLE        hdl;
TDRV005_STATUS        result;
TDRV005_MULTIPLEVALUES Values;

/*
** preload channel 0 and channel 5
*/
Values[0].Value = 0x00000000;
Values[5].Value = 0x50000000;

result = tdrv005GlobalCounterPreloadSet ( hdl,
                                           TDRV005_CH0 | TDRV005_CH5,
                                           Values);

if (result != TDRV005_OK)
{
    /* handle error */
}
```

RETURN VALUE

On success, TDRV005_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

| Error Code | Description |
|----------------------------|---|
| TDRV005_ERR_INVALID_HANDLE | The specified device handle is invalid |
| TDRV005_ERR_INVALID | Invalid parameter specified |
| TDRV005_ERR_BUSY | Channel is not configured to counter mode |

2.6.4 tdrv005GlobalCounterLoad

Name

tdrv005GlobalCounterLoad – globally load preload registers into counters

Synopsis

```
TDRV005_STATUS tdrv005GlobalCounterLoad
(
    TDRV005_HANDLE          hdl,
    unsigned char           Channels
)
```

Description

Perform a simultaneous preload of specified counter channels. The values stored in the corresponding preload registers are loaded into the specified counters simultaneously. The function returns immediately to the caller.

Parameters

hdl

This value specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

Channels

This value specifies the channels which should be preloaded. The pre-defined values (TDRV005_CH0 – TDRV005_CH5) must be used. Multiple channels may be OR'ed to one value.

Example

```
#include "tdrv005api.h"

TDRV005_HANDLE    hdl;
TDRV005_STATUS    result;

...
```

```
...

/*
** load channel 0 and channel 5
*/
result = tdrv005GlobalCounterLoad(hdl,
                                   TDRV005_CH0 | TDRV005_CH5);

if (result != TDRV005_OK)
{
    /* handle error */
}
```

RETURN VALUE

On success, TDRV005_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

| Error Code | Description |
|----------------------------|---|
| TDRV005_ERR_INVALID_HANDLE | The specified device handle is invalid |
| TDRV005_ERR_INVALID | Invalid parameter specified |
| TDRV005_ERR_BUSY | Channel is not configured to counter mode |

2.6.5 tdrv005GlobalMultipleChannelRead

Name

tdrv005GlobalMultipleChannelRead – read multiple channels simultaneously

Synopsis

```
TDRV005_STATUS tdrv005GlobalMultipleChannelRead
(
    TDRV005_HANDLE          hdl,
    unsigned char           Channels,
    TDRV005_MULTIPLEVALUES *MultipleValues
)
```

Description

Return the values of simultaneously sampled channels. The desired channel numbers must be supplied to this function as well as an array to store all channel values. The function returns to the caller after the read operation is finished.

Channels configured to SSI listen-only mode may not be used with this function.

Parameters

hdl

This value specifies the device handle to the hardware module retrieved by a call to the corresponding open-function.

Channels

This value specifies the channels which should be read simultaneously. The pre-defined values (TDRV005_CH0 – TDRV005_CH5) must be used. Multiple channels may be OR'ed to one value.

MultipleValues

This is a pointer to a TDRV005_MULTIPLEVALUES structure, where the read values are stored. The returned values are only valid for channels enabled by the parameter *Channels*. The TDRV005_MULTIPLEVALUES structure has the following layout:

```
typedef struct
{
    TDRV005_VALUE_BUF Channel[6];
} TDRV005_MULTIPLEVALUES;
```

Channel

This parameter is an array of a TDRV005_VALUE_BUF structure which holds the returned channel data. The value for channel 0 is returned at array index 0, channel 5's value is located at array index 5. The TDRV005_VALUE_BUF structure has the following layout:

```
typedef struct
{
    unsigned int    Value;
    unsigned int    Status;
} TDRV005_VALUE_BUF;
```

Value

This parameter holds the returned channel value.

Status

This parameter holds the returned channel status.

Example

```
#include "tdrv005api.h"

TDRV005_HANDLE        hdl;
TDRV005_STATUS        result;
TDRV005_MULTIPLEVALUES MultipleValues;

/*
** read channel 0 and channel 5 simultaneously
*/
result = tdrv005GlobalMultipleChannelRead( hdl,
                                           TDRV005_CH0 | TDRV005_CH5,
                                           &MultipleValues);

if (result == TDRV005_OK)
{
    printf("Channel(0) = 0x%08X\n", MultipleValues.Channel[0].Value);
    printf("Channel(5) = 0x%08X\n", MultipleValues.Channel[5].Value);
}
else
{
    /* handle error */
}
```

RETURN VALUE

On success, TDRV005_OK is returned. In the case of an error, the appropriate error code is returned by the function.

ERROR CODES

| Error Code | Description |
|----------------------------|--|
| TDRV005_ERR_INVALID_HANDLE | The specified device handle is invalid |
| TDRV005_ERR_INVALID | Invalid parameter specified |
| TDRV005_ERR_BUSY | A MultipleChannelRead job is already pending, or a channel is busy with an SSI job |
| TDRV005_ERR_TIMEOUT | Internal timeout. The values couldn't be retrieved within 2 seconds |

3 Appendix

3.1 Enable RTP-Support

Using TDRV005 devices tunneled from Real Time Processes (RTPs) is implemented. For this the "TEWS TDRV005 IOCTL command validation" must be enabled in system configuration.

The API source file "tdrv005api.c" must be added to the RTP-Project directory and build together with the RTP-application.

The definition of TVXB_RTP_CONTEXT must be added to the project, which is used to eliminate kernel headers, values and functions from the used driver files.

Find more detailed information in "TEWS TECHNOLOGIES VxWorks Device Drivers - Installation Guide".

All legacy functions, functions for version compatibility and debugging functions are not usable from RTPs.